



ACCESSORIES INCLUDED

2 PREMIUM+ REMOTES

Each button is independently programmable and backed by Security+ 2.0 technology.

TWO BUTTON WIRELESS WALL BUTTON Controls up to two garage door openers and is backed by Security+2.0 technology.

M828AU774

827AU

WEIGHT BAR

Helps stabilise the garage door when opening and closing.

SMART



MYQ COMPATIBLE TECHNOLOGY lets users create schedules, monitor, receive alerts and control the garage door opener away from home.1



■×

Î

SOFT-START AND SOFT-STOP for smooth operation.

POWERFUL ADD-ONS



MYQ CONNECTIVITY BUNDLE

Add monitoring and control away from home. Includes myQ Gateway and The Protector System™ (Safety IR Beams).

MYQ REMOTE LED LIGHT Ultra-bright LED light designed to illuminate your garage or workspace. Controlled by a garage door opener, remote control or myQ app.

E840M

WIRELESS SECURITY KEYPAD

Convenient and safe access to your garage without using a remote control or key.

E940M



SINGLE BUTTON REMOTE CONTROL WITH CAR VISOR CLIP Easily attaches to your car visor to control one garage door. Backed by Security+ 2.0 technology.



THREE BUTTON REMOTE CONTROL WITH CAR VISOR CLIP Easily attaches to your car visor to control up to three garage doors. Backed by Security+ 2.0 technology.

SAFE & SECURE

QUIET & RELIABLE

5-YEAR WARRANTY

smooth operation.



SECURITY+ 2.0° sends a new code with every remote click.

HEAVY-LIFTING POWER operates doors up to 100 kgs.



PREMIUM AUTOMATIC SAFETY REVERSE function will allow your garage door to stop and reverse automatically if obstructed going down or stop going up.

QUIET DC MOTOR eliminates noise and vibrations through the ceiling and provide



TIMER-TO-CLOSE automatically closes the door after a pre-set amount of time.²



IMPROVED TRANSMITTER RANGE has up to 18% better range meaning you can start opening your garage door sooner.3



AUTOMATIC FORCE SENSING monitors and adjusts the force needed to open your garage with each operation.



MANUAL RELEASE CORD allows you to open your garage door whenever needed.

gomerlin.com.au **■** gomerlin.co.nz

¹Additional purchase of Merlin myQ Gateway and Safety IR Beams accessories required to enable myQ functionality. Visit gomertin.com.au or gomertin.com.z for further information. ²Safety IR Beams must be installed to enable the use of Timer-to-Close. See User Guide for additional information. Smartphone not included. ³When compared to other available Merlin products.

SilentDrive Essential

ALL THE ESSENTIAL PERFORMANCE AND DESIGN FEATURES YOU NEED MR655MYQ







ROLLER GARAGE DOOR OPENER MYQ COMPATIBLE

GARAGE DOOR OPENER IS COMPATIBLE WITH MYQ

Additional purchase of The Protector System[™] and myQ Gateway is required

APP AVAILABLE ON:






- · Monitor and control your garage door away from home through the Merlin myQ app.
- Peace of mind knowing if your garage door is open or closed anywhere and any time.
- Receive real time alerts and notifications so you know when the garage door is opened or closed by loved ones



- · Pre-set times to automatically close your garage door at any time.
- See history records of your garage door open and close periods.
- Protect your loved ones and belongings with The Protector System™ (Safety IR Beams).
- Compatible Merlin myQ app available for smart devices including Apple Watch.

TYPICAL INSTALLATION - ROLLER DOORS



- Maximum lifting under spring tensions: 20 kg
- Suitable for steel spring balanced doors
- Door height: 4.5m; total door area: 16.5m²
- Single dwelling, max door weight up to 100 kg





SECURITY+ 2.0®

- · Encrypted rolling code across multiple frequencies.
- Security+ 2.0® technology virtually eliminates interference.





RADIO

- · Provides 2-way communication from rolling door opener and accessories.
- Receiver with 64 memory registers.



LIGHTING: LED LIGHTING

- · LED light turns on with activation.
- Garage illumination: 12 premium ultrabright LEDs.

STANDARD SPECIFICATIONS

- Input Voltage: 240V AC
- Rated door areas up to: 16.5m²
- Max door height: 4.5m
- Max door weight: 100 kg
- Max peak pulling force: 500N
- Max lift under spring tension: 20 kg
- · Minimum side room: 45mm
- Radio frequency: 433.30, 434.54 and 433.92 MHz with Security +2.0 technology.

- Noise rating 1M: 57DB
- Drum rotations: 4.5
- · 24V DC motor with thermal overload protection
- · Up to 64 memory registers
- Garage illumination: 12 premium ultrabright LEDs
- Compatible with myQ technology²





AUSTRALIA

Chamberlain Australia Pty Ltd PO Box 1446 Lane Cove NSW 1595 Australia

gomerlin.com.au 1800 638 234

NEW ZEALAND

Chamberlain New Zealand Ltd P0 Box 100-221 North Shore Auckland 0745 New Zealand

gomerlin.co.nz 0800 653 667

Engineered and designed by The Chamberlain Group, Inc. © Chamberlain Group 2019. All Rights Reserved. $^{\intercal}$ Trademark of The Chamberlain Group, Inc. $^{\circ}$ Registered Trademark of the Chamberlain Group.